

Profile Series/Die #	Width	Alloy/Temper	Overall Height	Fin Height	Base Height	Weight/Ft' Weight/In"	Approx C/W/3"	Outer Perimeter
A #22665	5.375"	6063-T5	1.375	1.000	.375	4.420/.37	1.15	51.587
B #24017	5.886"	6063-T6	1.270	1.000	.270	2.948/.25	1.75	39.594
C 23841	7.280"	6063-T6	1.300	1.000	.300	4.406/.37	1.30	51.491
D #23589	8.460"	6063-T6	1.300	1.000	.300	5.117/.43	1.10	59.581
E #24907	10.080"	6063-T6	2.875	2.500	.375	11.912/.99	0.80	137.749
F #24196	4.230"	6063-T5	1.050	0.750	.300	2.291/.19	2.15	24.611
G #24300	10.000"	6063-T6	1.300	1.000	.300	5.958/.50	0.90	68.021
H #24480	1.813"	6063-T5	1.250	0.950	.300	1.165/.10	4.50	15.153
I #24601	3.500"	6063-T5	1.050	0.750	.300	1.830/.15	2.50	18.885
J #24639	6.080"	6063-T6	0.500	0.250	.250	2.213/.18	2.95	20.016
K #24684	4.850"	6063-T5	0.805	0.660	.140	1.601/.13	2.12	31.100
L #24688	3.945"	6063-T6	2.875	2.500	.375	4.849/.40	1.45	57.344
M T-Slot #24706	8.460"	6063-T6	1.300	1.000	.300	5.496/.46	1.00	71.192
N #24884	4.600"	6063-T5	1.681	1.451	0.230	3.768/.31	1.40	60.253
P #24939	4.900"	6063-T6	1.300	1.000	.300	2.978/.25	1.68	35.270

